



PLUS ALKALINE BATTERY




Unit: mm(inch)


10.2 Discharge Resistance: 180 Ω Discharge Resistance, receiption per day Discharge Environment: $20 \pm 2^{\circ}$ C RH 45~75% 9.6 9.0 8.4 Voltage (V) 7.8 7.2 6.6 6.0 5.4 4.8 1 0 200 400 600 800 1000 **Discharge Time (min)**



6LF22

 $\begin{array}{l} \textbf{Chemical System :} Alkaline \\ \textbf{Zinc-Manganese Dioxide (Zn/MnO_2)} \\ \textbf{Camelion Model :} 6LF22 \\ \textbf{IEC No. :} 6LR61 \\ \textbf{ANSI/NEDA No. :} 1604A(9V) \\ \textbf{Average Weight :} 45.3g \\ \textbf{Dimension(LxWxH) :} 26.2^{\pm0.1} \times 17.2^{\pm0.1} \times 48.3^{\pm0.2} \text{mm} \\ 1.03^{\pm0.004} \times 0.69^{\pm0.004} \times 1.90^{\pm0.005} \text{ inch} \\ \textbf{Terminals :} Mininature Snap \\ \textbf{Nominal Voltage :} 9.0Volts \\ \textbf{Average Capacity :} 700 \text{ mAh to } 4.8 \text{ volts} \\ (20 \pm 2^{\circ} \mathbb{C}, \text{Rated capacity at } 25 \text{ mA continuous drain }) \\ \textbf{Jacket :} Aluminum Foil Label} \end{array}$





Notice:

Envoronmental elements comply with ROHS requirements. This information is subject to change without prior notice and for reference only. It should not be used as a product guarantee or warranty. For additional information, please contact with Vapex Technology Limited.

VAPEX TECHNOLOGY LIMITED.